

Sales Floor Area
77.82m²/838 sq ft

2301

NOTES: THIS DRAWING IS TO BE READ IN
CONJUNCTION WITH THE LINDEN HOMES
TECHNICAL SPECIFICATION.

ELEVATION LEGEND

c.l.	Centre line
M.J.B	Movement joint in Brick
M.J.R	Movement joint in Render / Recon Stone
RWP	Rainwater pipe
DPC	Damp proof course
FAF	Fan assisted flue
SVP	Soil vent pipe
(e)	Emergency egress window
(SG)	Safety glass to windows & doors
(ob)	Obscure glazing
*	Fixed casement
(g)	Guarding to inside of window
G	Gas meter box
	Extract fan ducted within floor zone
	Tile vent for extract fan or SVP.

ELEVATION LEGEND

c.l.	Centre line
M.J.B	Movement joint in Brick
M.J.R	Movement joint in Render / Recon Stone
RWP	Rainwater pipe
DPC	Damp proof course
FAF	Fan assisted flue
SVP	Soil vent pipe
(e)	Emergency egress window
(SG)	Safety glass to windows & doors
(ob)	Obscure glazing
*	Fixed casement
(g)	Guarding to inside of window
G	Gas meter box
	Extract fan ducted within floor zone
	Tile vent for extract fan or SVP.

Plots

As: 403

Opp: 402

Linden GallifordTry
HOMES

© 2015 Linden Limited All Rights Reserved

PROJECT

Affordable Homes Layouts

For Linden Homes

Boorley Green Parcel B6

DRAWING


Front Elevation

House Type 2301

SCALE	DATE	AUTHOR	CHK'D
1:50 @ A3	April 2019	SGS	WKB

JOB NO.	DRAWING NO.	REV
LHS307	2301-600	P12

CLIENT REF.



Front Elevation

Front Elevation

NOTE: For bed joint reinforcement,
Elevations shown as Brick, no bed joint reinforcement
required. Setting out for Render/Recon Stone coursing
heights may be adjusted depending on openings.

NOTE: Emergency egress windows to have a clear
opening of 450 x 735mm (0.33m²), openable part
of windows to be located within 800 to 1100mm
from finished floor level.

NOTE: For rainwater downpipe locations,
refer to plot specific drawings.

NOTE: For recon stone units, ensure
mortar is colour matched to the stone.

Sales Floor Area
77.82m²/838 sq ft

2301

NOTES: THIS DRAWING IS TO BE READ IN CONJUNCTION WITH THE LINDEN HOMES TECHNICAL SPECIFICATION.

ELEVATION LEGEND

c.l.	Centre line
M.J.B	Movement joint in Brick
M.J.R	Movement joint in Render / Recon Stone
RWP	Rainwater pipe
DPC	Damp proof course
FAF	Fan assisted flue
SVP	Soil vent pipe
(e)	Emergency egress window
(SG)	Safety glass to windows & doors
(ob)	Obscure glazing
*	Fixed casement
(g)	Guarding to inside of window
G	Gas meter box
	Extract fan ducted within floor zone
	Tile vent for extract fan or SVP.

ELEVATION LEGEND

c.l.	Centre line
M.J.B	Movement joint in Brick
M.J.R	Movement joint in Render / Recon Stone
RWP	Rainwater pipe
DPC	Damp proof course
FAF	Fan assisted flue
SVP	Soil vent pipe
(e)	Emergency egress window
(SG)	Safety glass to windows & doors
(ob)	Obscure glazing
*	Fixed casement
(g)	Guarding to inside of window
G	Gas meter box
	Extract fan ducted within floor zone
	Tile vent for extract fan or SVP.

Plots

As: 403

Opp: 402

Linden GallifordTry
HOMES

© 2015 Linden Limited All Rights Reserved

PROJECT

Affordable Homes Layouts

For Linden Homes

Boorley Green Parcel B6

DRAWING


Side Elevation

House Type 2301

SCALE	DATE	AUTHOR	CHK'D
1:50 @ A3	April 2019	SGS	WKB

JOB NO.	DRAWING NO.	REV
LHS307	2301-601	P12

CLIENT REF.



Side Elevation

NOTE: For bed joint reinforcement. Elevations shown as Brick, no bed joint reinforcement required. Setting out for Render/Recon Stone coursing heights may be adjusted depending on openings.

NOTE: Emergency egress windows to have a clear opening of 450 x 735mm (0.33m²), openable part of windows to be located within 800 to 1100mm from finished floor level.

NOTE: For rainwater downpipe locations, refer to plot specific drawings.


NOTE: For recon stone units, ensure mortar is colour matched to the stone.

Sales Floor Area

77.82m²/838 sq ft

2301

NOTES: THIS DRAWING IS TO BE READ IN
CONJUNCTION WITH THE LINDEN HOMES
TECHNICAL SPECIFICATION.



ELEVATION LEGEND

c.l.	Centre line
M.J.B	Movement joint in Brick
M.J.R	Movement joint in Render / Recon Stone
RWP	Rainwater pipe
DPC	Damp proof course
FAF	Fan assisted flue
SVP	Soil vent pipe
(e)	Emergency egress window
(SG)	Safety glass to windows & doors
(ob)	Obscure glazing
*	Fixed casement
(g)	Guarding to inside of window
G	Gas meter box
	Extract fan ducted within floor zone
	Tile vent for extract fan or SVP.

ELEVATION LEGEND

c.l.	Centre line
M.J.B	Movement joint in Brick
M.J.R	Movement joint in Render / Recon Stone
RWP	Rainwater pipe
DPC	Damp proof course
FAF	Fan assisted flue
SVP	Soil vent pipe
(e)	Emergency egress window
(SG)	Safety glass to windows & doors
(ob)	Obscure glazing
*	Fixed casement
(g)	Guarding to inside of window
G	Gas meter box
	Extract fan ducted within floor zone
	Tile vent for extract fan or SVP.

Plots

As: 403

Opp: 402

Linden GallifordTry
HOMES

© 2015 Linden Limited All Rights Reserved

PROJECT

Affordable Homes Layouts

For Linden Homes

Boorley Green Parcel B6

DRAWING

Rear Elevation

House Type 2301

SCALE	DATE	AUTHOR	CHK'D
1:50 @ A3	April 2019	SGS	WKB

JOB NO.	DRAWING NO.	REV
LHS307	2301-602	P12

CLIENT REF.

NOTE: For bed joint reinforcement.
Elevations shown as Brick, no bed joint reinforcement required. Setting out for Render/Recon Stone coursing heights may be adjusted depending on openings.

NOTE: Emergency egress windows to have a clear opening of 450 x 735mm (0.33m²), openable part of windows to be located within 800 to 1100mm from finished floor level.

NOTE: For rainwater downpipe locations, refer to plot specific drawings.

NOTE: For recon stone units, ensure mortar is colour matched to the stone.

Rear Elevation