FOUL DRAINAGE MANHOLE SCHEDULE

REFERENCE	Cover Level (m)	Invert Level (m)	Depth to Soffit (m)	Size (mm)	Type	Cover Grade
Ref6002 Existing Manhole	21.32	19.57	1.60	To be confirmed		Existing
FA	22.06	20.143	1.767	1200 diameter	2	D400
FB	22.34	20.468	1.722	1200 diameter	2	D400
F1	22.45	20.568	1.732	1200 diameter	2	D400
F2	22.47	20.733	1.587	600 diameter	3	D400
F3	22.35	20.829/21.320	1.371/0.88	600 diameter	3	D400
F4	22.22	21.044/21.094	1.026	600 diameter	3	D400
F5	22.30	21.071	1.079	1200 diameter	2	D400
F6	22.34	20.493	1.697	600 diameter	2	D400
F7	22.07	20.369	1.551	600 diameter	3	D400
F8	21.97	20.455	1.365	600 diameter	3	D400
F9	21.67	20.661/20.711	0.859	600 diameter	3	D400
F10	22.20	19.809	2.241	600 diameter	3	D400
F11	22.30	19.724	2.426	600 diameter	3	D400
F12	21.60	19.475/19.525	1.975	600 diameter	3	D400
F13	20.50	19.101	1.257	1200 diameter	2	D400
F14	20.45	19.052/19.102	1.248	600 diameter	3	D400
F15	20.20	18.752/18.802	1.298	600 diameter	3	D400
F16	20.26	18.620	1.490	600 diameter	3	D400
F17	20.36	18.498/18.548	1.712	600 diameter	3	D400
F18	20.46	18.000/19.100	2.310/1.210	1200 diameter	2	D400
F18A	20.50	17.916	2.434	600 diameter	3	D400
F19	21.27	20.100/20.150	1.184	600 diameter	3	D400
F20	21.52	20.300/20.350	1.070	600 diameter	3	D400
F21	23.00	22.450	0.250	250 diameter	4	B125
F22	23.00	22.20	0.700	450 diameter	3	B125
F23	23.00	22.075/22.025	0.825	450 diameter	3	B125
F24	22.90	21.870	0.880	450 diameter	3	B125
F25	22.90	21.820	0.930	450 diameter	3	B125
F26	22.62	21.520	0.950	450 diameter	3	B125
F27	22.53	20.925/20.875	1.505	450 diameter	3	B125
F28	22.11	21.100/21.050	0.91	450 diameter	3	B125
F29	21.94	21.260	0.58	450 diameter	3	B125
F30	21.51	20.647	0.763	450 diameter	3	B125
F31	21.525	20.652	0.723	450 diameter	3	B125
F32	21.50	20.699	0.651	450 diameter	3	B125
F33	21.50	20.820/20.770	0.580	450 diameter	3	B125
F34	21.64	20.985	0.555	450 diameter	3	B125
F35	21.40	20.700	0.600	450 diameter	3	B125
F36	21.38	20.400	0.680	450 diameter	3	B125
F37	21.65	20.400	1.150	450 diameter	3	B125
F38	21.55	20.850	0.600	450 diameter	3	B125
F39	21.00	20.350	0.550	450 diameter	3	B125
F40	20.53	19.950	0.480	450 diameter	3	B125
F41	20.50	19.243	1.157	450 diameter	3	B125
F42	21.02	19.900	0.912	450 diameter	3	B125
F43	21.22	20.475	0.645	450 diameter	3	B125
F44	21.70	21.000	0.600	450 diameter	3	B125
F45	21.80	21.100	0.600	450 diameter	3	B125
F46	22.40	21.675	0.625	450 diameter	3	B125
F47	22.50	21.800	0.600	450 diameter	3	B125
F48	22.40	21.435	0.865	450 diameter	3	B125
F49	21.10	20.575	0.425	450 diameter	3	B125
F50	21.52	20.488	0.932	450 diameter	3	B125
F51	21.60	19.604	1.896	450 diameter	3	B125
F52	22.05	21.400	0.550	450 diameter	3	B125
F53	22.38	21.258	1.022	450 diameter	3	B125
F54	22.50	21.637/21.587	0.763	450 diameter	3	B125
F55	22.535	21.800	0.635	450 diameter	3	B125
F56	22.55	21.400	1.000	450 diameter	3	B125
F57	22.75	21.550/21.500	1.100	450 diameter	3	B125
F58	23.00	21.700	1.200	450 diameter	3	B125
F59	23.00	22.300	0.600	450 diameter	3	B125
F60	22.95	22.300	0.550	450 diameter	3	B125
F61	22.90	22.200	0.600	450 diameter	3	B125
F62	22.45	21.700	0.650	450 diameter	3	B125
F63	22.40	21.583	0.717	450 diameter	3	B125
F64	21.95	21.350	0.500	450 diameter	3	B125
F65	21.55	20.400	1.050	450 diameter	3	B125
F66	21.20	20.325	0.775	450 diameter	3	B125
F67	21.10	20.213	0.787	450 diameter	3	B125
F68	20.90	20.078	0.722	450 diameter	3	B125
F69	20.80	19.956/19.906	0.744	450 diameter	3	B125
F70	20.70	19.832	0.718	450 diameter	3	B125
F71	20.63	19.747	0.733	450 diameter	3	B125
F72	20.60	19.850	0.600	450 diameter	3	B125
F73	20.45	19.598	0.707	450 diameter	3	B125
F74	20.40	19.780	0.520	450 diameter	3	B125
F75	20.40	19.800	0.500	450 diameter	3	B125
F76	20.40	19.617	0.683	450 diameter	3	B125
F77	20.60	19.800	0.700	450 diameter	3	B125
F78	21.00	20.128	0.772	450 diameter	3	B125
F79	20.88	20.000	0.780	450 diameter	3	B125
F80	21.70	21.050	0.550	450 diameter	3	B125
F81	20.68	20.950	0.630	450 diameter	3	B125
F82	21.50	20.790/20.740	0.610	450 diameter	3	B125
F83	21.475	20.900	0.475	450 diameter	3	B125
F84	21.65	20.850	0.700	450 diameter	3	B125
F85	21.75	21.000	0.650	450 diameter	3	B125
F86	22.40	20.800	0.683	450 diameter	3	B125
F87	22.55	21.800	0.650	450 diameter	3	B125
F88	22.90	22.300	0.500	450 diameter	3	B125
F89	22.55	21.740	0.710	450 diameter	3	B125

PUMPING STATION DETAILS

REFERENCE	Cover Level (m)	Invert Level Incoming pipe (m)	Depth to Soffit (m)	Wet well base (TBC) (m)	Size (mm)	Cover Grade
PS1	20.65	15.65	4.775	14.75	2.10 diameter	D400

FOUL DRAINAGE MANHOLE SCHEDULE

REFERENCE	Cover Level (m)	Invert Level (m)	Depth to Soffit (m)	Size (mm)	Type	Cover Grade
F1/1	22.60	22.000	0.500	250 diameter	4	A15
F1/2	22.60	22.000	0.500	250 diameter	4	A15
F1/3	22.60	22.000	0.500	250 diameter	4	A15
F1/4	22.60	22.000	0.500	250 diameter	4	A15
F1/5	22.60	22.000	0.500	250 diameter	4	A15
F1/6	22.60	22.000	0.500	250 diameter	4	A15
F1/7	22.95	22.350	0.365	250 diameter	4	A15
F1/8	22.95	22.350	0.375	250 diameter	4	A15
F1/9	22.95	22.350	0.360	250 diameter	4	A15
F1/10	22.95	22.350	0.500	250 diameter	4	A15
F1/11	22.90	22.300	0.500	250 diameter	4	A15
F1/12	22.90	22.300	0.500	250 diameter	4	A15
F1/13	22.90	22.300	0.500	250 diameter	4	A15
F1/14	22.90	22.300	0.500	250 diameter	4	A15
F1/15	22.85	22.250	0.500	250 diameter	4	A15
F1/16	22.85	22.250	0.500	250 diameter	4	A15
F1/17	22.85	22.250	0.500	250 diameter	4	A15
F1/18	22.475	21.875	0.500	250 diameter	4	A15
F1/19	22.475	21.875	0.500	250 diameter	4	A15
F1/20	21.95	21.350	0.500	250 diameter	4	A15
F1/21	21.95	21.350	0.500	250 diameter	4	A15
F2/1	22.425	21.825	0.500	250 diameter	4	A15
F2/2	22.275	21.675	0.500	250 diameter	4	A15
F2/3	22.275	21.675	0.500	250 diameter	4	A15
F2/4	22.275	21.675	0.500	250 diameter	4	A15
F2/5	22.275	21.675	0.500	250 diameter	4	A15
F2/6	21.95	21.375	0.475	250 diameter	4	A15
F2/7	21.600	21.000	0.500	250 diameter	4	A15
F2/8	21.600	21.000	0.500	250 diameter	4	A15
F2/9	21.600	21.000	0.500	250 diameter	4	A15
F2/10	21.075	20.475	0.500	250 diameter	4	A15
F2/11	21.075	20.475	0.500	250 diameter	4	A15
F2/12	21.075	20.475	0.500	250 diameter	4	A15
F2/13	22.05	21.450	0.500	250 diameter	4	A15
F2/14	22.05	21.450	0.500	250 diameter	4	A15
F2/15	21.625	21.025	0.500	250 diameter	4	A15
F2/16	21.400	20.800	0.500	250 diameter	4	A15
F2/17	20.925	20.325	0.500	250 diameter	4	A15
F2/18	20.925	20.325	0.500	250 diameter	4	A15
F2/19	20.925	20.325	0.500	250 diameter	4	A15
F2/20	20.925	20.325	0.500	250 diameter	4	A15
F2/21	20.70	20.100	0.500	250 diameter	4	A15
F3/1	21.425	21.825	0.500	250 diameter	4	A15
F3/2	21.425	21.825	0.500	250 diameter	4	A15
F3/3	21.425	21.825	0.500	250 diameter	4	A15
F3/4	21.425	21.825	0.500	250 diameter	4	A15
F3/5	21.425	21.825	0.500	250 diameter	4	A15
F3/6	21.425	21.825	0.500	250 diameter	4	A15
F3/7	22.55	21.950	0.500	250 diameter	4	A15
F3/8	22.55	21.950	0.500	250 diameter	4	A15
F3/9	22.930	22.300	0.500	250 diameter	4	A15
F3/10	22.930	22.300	0.500	250 diameter	4	A15
F3/11	22.30	21.500	0.700	250 diameter	4	A15
F3/12	22.55	21.950	0.500	250 diameter	4	A15
F3/13	22.55	21.950	0.500	250 diameter	4	A15
F3/14	22.55	21.950	0.500	250 diameter	4	A15
F3/15	22.55	21.950	0.500	250 diameter	4	A15
F3/16	22.88	22.300	0.480	250 diameter	4	A15
F3/17	22.80	22.300	0.400	250 diameter	4	A15
F3/18	22.90	22.300	0.500	250 diameter	4	A15
F4/1	21.75	21.150	0.500	250 diameter	4	A15
F4/2	21.55	20.950	0.500	250 diameter	4	A15
F4/3	21.375	20.800	0.475	250 diameter	4	A15
F4/4	21.375	20.900	0.375	250 diameter	4	A15
F4/5	21.70	21.100	0.500	250 diameter	4	A15
F4/6	21.70	21.100	0.500	250 diameter	4	A15
F4/7	22.30	21.700	0.500	250 diameter	4	A15
F4/8	22.30	21.700	0.500	250 diameter	4	A15
F4/9	21.95	21.350	0.500	250 diameter	4	A15
F4/10	21.70	21.000	0.500	250 diameter	4	A15
F4/11	21.125	20.525	0.500	250 diameter	4	A15
F4/12	21.125	20.525	0.500	250 diameter	4	A15
F4/13	20.80	20.200	0.500	250 diameter	4	A15
F4/14	20.65	20.050	0.500	250 diameter	4	A15
F4/15	20.65	20.050	0.500	250 diameter	4	A15
F5/1	20.50	19.900	0.500	250 diameter	4	A15
F5/2	20.50	19.900	0.500	250 diameter	4	A15
F5/3	20.40	19.800	0.500	250 diameter	4	A15
F5/4	20.40	19.800	0.500	250 diameter	4	A15
F5/5	20.40	19.800	0.500	250 diameter	4	A15
F5/6	20.40	19.800	0.500	250 diameter	4	A15
F5/7	20.40	19.800	0.500	250 diameter	4	A15
F5/8	20.50	19.900	0.500	250 diameter	4	A15
F5/9	20.50	19.900	0.500	250 diameter	4	A15
F5/10	20.50	19.900	0.500	250 diameter	4	A15
F5/11	19.60	19.000	0.500	250 diameter	4	A15
F5/12	19.60	19.000	0.500	250 diameter	4	A15
F5/13	20.15	19.550	0.500	250 diameter	4	A15
F5/14	20.15	19.550	0.500	250 diameter	4	A15
F5/15	20.15	19.550	0.500	250 diameter	4	A15
F5/16	20.15	19.550	0.500	250 diameter	4	A15
F5/17	20.15	19.550	0.500	250 diameter	4	A15
F5/18	20.15	19.550	0.500	250 diameter	4	A15
F5/19	20.30	19.700	0.500	250 diameter	4	A15
F5/20	20.30	19.700	0.500	250 diameter	4	A15
F5/21	20.30	19.700	0.500	250 diameter	4	A15
F5/22	20.55	19.950	0.500	250 diameter	4	A15
F5/23	21.00	20.400	0.500	250 diameter	4	A15
F5/24	20.30	20.700	0.500	250 diameter	4	A15
F5/25	20.30	20.700	0.500	250 diameter	4	A15
F5/26	20.30	20.700	0.500	250 diameter	4	A15
F5/27	21.50	20.900	0.500	250 diameter	4	A15
F5/28	21.50	20.850	0.550	250 diameter	4	A15
F5/29	21.50	20.850	0.550	250 diameter	4	A15
F5/30	21.50	20.900	0.500	250 diameter	4	A15
F6/1	21.65	21.050	0.500	250 diameter	4	A15
F6/2	21.45	20.850	0.500	250 diameter	4	A15
F6/3	21.45	20.850	0.500	250 diameter	4	A15

SURFACE WATER DRAINAGE RODDING EYE SCHEDULE

REFERENCE	Cover Level (m)	Invert Level (m)	Depth to Soffit (m)	Type	Cover Grade
R1	22.475	22.000	0.375	RE	B125
R2	22.475	22.000	0.375	RE	B125
R3	22.90	22.400	0.400	RE	B125
R4	22.90	22.400	0.400	RE	B125
R5	22.50	21.950	0.450	RE	B125
R6	22.60	22.100	0.400	RE	B125
R7	22.60	22.100	0.400	RE	B125
R8	22.85	22.350	0.400	RE	B125
R9	22.85	22.350	0.400	RE	B125
R10	22.425	22.000	0.325	RE	B125
R11	22.425	22.000	0.325	RE	B125
R12	20.400	21.800	0.500	RE	B125
R13	22.25	20.700	0.450	RE	B125
R14	21.60	21.100	0.400	RE	B125
R15	21.075	20.500	0.475	RE	B125
R16	21.075	20.500	0.475	RE	B125
R17	21.45	21.000	0.350	RE	B125
R18	21.45	21.000	0.350	RE	B125
R19	21.65	21.000	0.550	RE	B125
R20	21.525	21.025	0.400	RE	B125
R21	21.525	21.025	0.400	RE	B125
R22	21.50	21.000	0.400	RE	B125
R23	21.50	21.000	0.400	RE	B125
R24	22.10	21.650	0.350	RE	B125
R25	21.60	21.100	0.400	RE	B125
R26	21.17	20.550	0.520	RE	B125
R27	20.70	20.100	0.500	RE	B125
R28	21.30	20.600	0.600	RE	B125
R29	21.300	20.500	0.700	RE	B125
R30	20.55	20.000	0.450	RE	B125
R31	20.55	20.000	0.450	RE	B125
R32	20.15	19.630	0.420	RE	B125
R33	20.15	19.680	0.370	RE	B125
R34	19.735	19.393	0.242	RE	B125
R35	20.50	20.000	0.400	RE	B125
R36	20.50	20.000	0.400	RE	B125
R37	20.40	19.900	0.400	RE	B125
R38	20.40	19.900	0.400	RE	B125
R39	20.400	19.900	0.400	RE	B125
R40	20.400	19.900	0.400	RE	B125
R41	20.400	19.900	0.400	RE	B125
R42	20.50	19.900	0.500	RE	B125
R43	20.500	19.900	0.500	RE	B125
R44	20.70	20.100	0.500	RE	B125
R45	21.025	20.580	0.365	RE	B125
R46	21.36	20.630	0.630	RE	B125
R47	21.55	21.000	0.450	RE	B125
R48	21.80	21.300	0.400	RE	B125
R49	21.70	21.250	0.350	RE	B125
R50	21.70	21.250	0.350	RE	B125
R51	21.93	21.300	0.530	RE	B125
R52	22.235	21.600	0.535	RE	B125
R53	20.535	22.000	0.435	RE	B125
R54	22.915	22.350	0.465	RE	B125
R55	22.90	22.350	0.450	RE	B125
R56	22.285	21.750	0.435	RE	B125
R57	21.87	21.200	0.570	RE	B125
R58	21.41	21.000	0.310	RE	B125
R59	21.11	20.500	0.510	RE	B125
R60	20.785	20.200	0.485	RE	B125
R61	20.80	20.350	0.350	RE	B125
R62	20.70	20.000	0.600	RE	B125
R63	21.95	21.450	0.400	RE	B125
R64	21.95	21.450	0.400	RE	B125

SURFACE WATER DRAINAGE MANHOLE SCHEDULE

REFERENCE	Cover Level (m)	Invert Level (m)	Depth to Soffit (m)	Size (mm)	Type	Cover Grade
S1	21.90	20.60	1.150	450 diameter	5	D400
S2	21.70	19.902/19.827	1.648	600 diameter	5	D400
S3	21.55	20.226/20.176	1.124	450 diameter	5	D400
S4	21.65	19.807/19.732	1.618	1200 diameter	6	D400
S5	21.25	19.593/19.743/20.354	1.357	1200 diameter	6	D400
S6	20.40	19.354/19.279 19.504/19.429	0.746	1200 diameter	6	D400
S7	22.00	20.127/20.202	1.648	600 diameter	5	D400
S8	20.55	19.473	0.852	1200 diameter	6	D400
S9	20.25	19.167/19.092	0.708	1200 diameter	6	D400
S10	20.20	19.048/19.348	0.702	1200 diameter	6	D400
S11	20.25	19.021	0.779	1200 diameter	6	D400
S12	20.28	18.997/19.297	0.833	1200 diameter	6	D400
S13	20.30	18.967	0.883	1200 diameter	6	D400
S14	20.38	18.940/19.240	0.990	1200 diameter	6	D400
S15	20.50	18.883/19.183	1.167	1200 diameter	6	D400
S16	20.40	18.061	2.189	450 diameter	3	B125
S17	22.45	20.100/21.075	2.200	600 diameter	5	D400
S18	22.35	20.895/21.400	1.230	600 diameter	5	D400
S19	22.27	20.830	1.215	600 diameter	5	D400
S20	22.05	20.673/20.748	1.077	1200 diameter	6	D400
S21	21.85	20.474	1.226	600 diameter	5	D400
S22	21.55	20.310	1.090	600 diameter	5	D400
S23	22.30	20.573/20.498	1.427	1200 diameter	6	D400
S24	22.65	20.418/20.643	1.857	1200 diameter	6	D400
S25	22.95	20.354/21.062	2.221	1200 diameter	6	D400
S26	23.05	21.278	1.622	450 diameter	5	D400
S27	23.00	21.312	1.538	450 diameter	3	D400
S28	22.65	21.450	1.050	450 diameter	3	D400
S29	22.90	21.700/21.750	1.050	450 diameter	3	B125
S30	22.65	20.258/20.183	2.017	1200 diameter	6	D400
S31	21.30	20.027	0.823	1200 diameter	6	D400
SA	22.40	21.175	1.075	600 diameter	5	D400

SURFACE WATER DRAINAGE MANHOLE SCHEDULE

REFERENCE	Cover Level (m)	Invert Level (m)	Depth to Soffit (m)	Size (mm)	Type	Cover Grade
S32	22.60	21.528	0.922	450 diameter	3	B125
S33	22.65	21.562	0.938	450 diameter	3	B125
S34	22.60	21.650	0.800	450 diameter	3	B125
S35	22.90	21.750/21.800	1.000	450 diameter	3	B125
S36	23.00	22.070	0.780	450 diameter	3	B125
S37	23.00	22.200	0.700	450 diameter	3	B125
S38	23.10	22.290	0.710	450 diameter	3	B125
S39	22.90	22.370	0.430	450 diameter	3	B125
S40	22.835	22.240	0.495	450 diameter	3	B125
S41	22.985	22.080	0.805	450 diameter	3	B125
S42	22.50	21.600	0.750	450 diameter	3	B125
S43	22.55	21.650	0.750	450 diameter	3	B125
S44	22.90	22.200	0.550	450 diameter	3	B125
S45	22.635	21.800	0.685	450 diameter	3	B125
S46	22.50	18.910	0.510	450 diameter	3	B125
S47	22.50	21.110	1.240	450 diameter	3	B125
S48	22.55	20.200	2.200	450 diameter	3	B125
S49	22.78	21.150	1.480	450 diameter	3	B125
S50	22.87	20.692/21.453	2.028/1.267	450 diameter	3	B125
S51		NOT USED				
S52	22.90	22.000	0.800	450 diameter	3	B125
S53	22.95	21.838/21.788	1.012	450 diameter	3	B125
S54	22.92	22.250	0.570	450 diameter	3	B125
S55	22.45	21.890	0.460	450 diameter	3	B125
S56	22.50	21.790	0.610	450 diameter	3	B125
S57	22.475	21.890	0.485	450 diameter	3	B125
S58	21.95	20.708	1.142	450 diameter	3	B125
S59	22.00	20.691/20.641	1.209	450 diameter	3	B125
S60	21.65	20.654	0.896	450 diameter	3	B125
S61	21.65	20.700	0.850	450 diameter	3	B125
S62	21.45	20.880	0.470	450 diameter	3	B125
S63	21.60	20.724/20.674	0.776	450 diameter	3	B125

SURFACE WATER DRAINAGE MANHOLE SCHEDULE

REFERENCE	Cover Level (m)	Invert Level (m)	Depth to Soffit (m)	Size (mm)	Type	Cover Grade
S64	20.95	20.220/20.270	0.580	450 diameter	3	B125
S65	21.06	20.400	0.560	450 diameter	3	B125
S66	22.10	20.645/20.695	1.305	450 diameter	3	B125
S67	22.45	21.500	0.850	450 diameter	3	B125
S68	22.50	21.650	0.750	450 diameter	3	B125
S69	20.60	19.800	0.700	450 diameter	3	B125
S70	20.90	20.000	0.800	450 diameter	3	B125
S71	21.00	20.439/20.389	0.461	450 diameter	3	B125
S72	21.60	20.269	1.181	450 diameter	3	B125
S73	22.05	21.550	0.500	450 diameter	3	B125
S74	21.85	21.200	0.550	450 diameter	3	B125
S75	21.60	20.530/20.580	0.920	450 diameter	3	B125
S76	21.50	20.497/20.447	0.903	450 diameter	3	B125
S77	21.375	20.377	0.848	450 diameter	3	B125
S78	21.30	20.460/20.410	0.740	450 diameter	3	B125
S79	21.74	21.120	0.520	450 diameter	3	B125
S80	21.70	21.000	0.600	450 diameter	3	B125
S81	21.65	21.135	0.415	450 diameter	3	B125
S82	22.10	21.000	1.000	450 diameter	3	B125
S83	22.25	20.600	1.550	450 diameter	3	B125
S84	22.35	21.400	0.850	450 diameter	3	B125
S85	22.60	21.650	0.850	450 diameter	3	B125
S86	22.35	21.100	1.100	450 diameter	3	B125
S87	22.55	21.030	1.370	450 diameter	3	B125
S88	22.75	21.600	1.000	450 diameter	3	B125
S89	22.90	22.200	0.550	450 diameter	3	B125
S90	22.72	21.700	0.870	450 diameter	3	B125
S91	22.30	21.682	0.518	450 diameter	3	B125
S92	22.15	21.050/21.000	1.000	450 diameter	3	B125
S93	21.95	20.990/20.940	0.860	450 diameter	3	B125
S94	21.85	21.200	0.550	450 diameter	3	B125
S95	21.60	20.920/20.870	0.580	450 diameter	3	B125

SURFACE WATER DRAINAGE MANHOLE SCHEDULE

REFERENCE	Cover Level (m)	Invert Level (m)	Depth to Soffit (m)	Size (mm)	Type	Cover Grade
S96	21.15	20.000/19.950	1.050	450 diameter	3	B125
S97	21.00	20.100	0.800	450 diameter	3	B125
S98	20.88	20.250	0.530	450 diameter	3	B125
S99	20.71	19.70	0.910	450 diameter	3	B125
S100	20.60	19.600	0.900	450 diameter	3	B125
S101	20.70	19.350/19.300	1.250	450 diameter	3	B125
S102	20.70	19.500	1.100	450 diameter	3	B125
S103	20.60	19.400/19.450	1.050	450 diameter	3	B125
S104	20.50	19.800	0.600	450 diameter	3	B125
S105	20.40	19.600/19.650	0.650	450 diameter	3	B125
S106	20.40	19.800	0.500	450 diameter	3	B125
S107	20.40	19.780	0.520	450 diameter	3	B125
S108	20.35	19.650/19.700	0.550	450 diameter	3	B125
S109	20.40	19.780	0.520	450 diameter	3	B125
S110	20.50	19.880	0.520	450 diameter	3	B125
S111	20.40	19.730/19.780	0.520	450 diameter	3	B125
S112	20.50	19.880	0.600	450 diameter	3	B125
S113	21.50	20.306/20.356	1.044	450 diameter	3	B125
S114	21.65	20.600	0.950	450 diameter	3	B125
S115	21.525	20.925	0.500	450 diameter	3	B125
S116	21.485	20.400	0.985	450 diameter	3	B125
S117	21.30	20.150/20.100	1.050	450 diameter	3	B125
S118	21.00	20.400	0.500	450 diameter	3	B125
S119	21.10	20.300	0.700	450 diameter	3	B125
S120	20.75	19.900	0.750	450 diameter	3	B125
S121	22.55	19.820	0.630	450 diameter	3	B125
S122	20.30	19.530/19.580	0.620	450 diameter	3	B125
S123	20.28	19.700	0.480	450 diameter	3	B125
S124	20.28	19.605	0.575	450 diameter	3	B125
S125	20.28	19.755	0.425	450 diameter	3	B125
S126	20.28	19.840	0.340	450 diameter	3	B125
S127	20.24	19.600	0.540	450 diameter	3	B125

SURFACE WATER DRAINAGE MANHOLE SCHEDULE

REFERENCE	Cover Level (m)	Invert Level (m)	Depth to Soffit (m)	Size (mm)	Type	Cover Grade
S128	20.13	19.600	0.430	450 diameter	3	B125
S129	20.13	19.510/19.469	0.520	450 diameter	3	B125
S129A	20.85	19.469/19.419	1.281	450 diameter	3	B125
S130	20.12	19.542	0.478	450 diameter	3	B125
S131	20.13	19.462/19.412	0.568	450 diameter	3	B125
S132	20.15	19.580	0.470	450 diameter	3	B125
S133	20.15	19.381	0.619	450 diameter	3	B125
S134	20.00	19.360	0.540	450 diameter	3	B125
S135	19.60	18.850	0.600	450 diameter	3	B125
S136	19.60	18.740	0.760	450 diameter	3	B125
S137	19.50	18.000	1.350	450 diameter	5	B125
S138	20.20	17.980	2.070	450 diameter	3	B125
S139	20.40	18.010	2.240	450 diameter	3	B125
DD1	20.00	17.862	1.988	Downstream Defender		B125

iNFORMATION TO BE READ IN CONJUCTION WITH DRAINAGE LAYOUT DRAWINGS KNC2114-502-01 & KNC2114-502-02

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION
CDM Regulations 2015

In addition to the hazards/risks normally associated with the type of work detailed on this drawing note should be made of the following:

- Working in vicinity of live highway
- Services to be located prior to any excavation work being undertaken
- Working on live foul sewers
- Deep excavations

It is assumed that all works will be carried out by a competent contractor working, where appropriate, to an approved method statement. Contractor is not relieved of any of his obligations under all applicable health and safety regulations.

Rev.	Date	Details	Initials
B	09.01.23	Adjustments based on re-design	KN
A	18.12.22	First Issue	KN

Drawing Status
PRELIMINARY FOR TENDER

Project
GRANGE ROAD
NETLEY ABBEY

Client
ELIVIA HOMES

KAZYS NARBUTAS CONSULTING
Civil Engineering Consultant
Unit 24b, Romsey Industrial Estate, Greatbridge Road, Romsey, Hants. SO51 0HE
Telephone: 01794 223146 Email: kazys.n@knc.email

Drawing Title
Engineering Details
Drainage Schedules

Drawn	Checked	Scales	Paper Size	Date
KN		NTS	A1	12.22
Job No.		Drawing No.		Revision
KNC2114		502-03		B

This drawing is the copyright of Kazys Narbutas Consulting and may not be copied, altered or reproduced in any form or passed to a third party without the consent of Kazys Narbutas Consulting. Do not scale from this drawing, use figured dimensions only.
Dimensions should be checked and verified on site and any discrepancies should be reported to Escher Silverman as soon as possible.