

NHBC - CHAPTER 10.2.6 - TABLE 3

Minimum sub-base thickness for paved areas.		
California Bearing Ratio (CBR) Values	Minimum thickness (mm) of Sub-Base (Consolidated in accordance with MOWV Volume 1 clause 801, table 8/1)	
	Without Geotextile Underneath	With Geotextile Underneath
Less Than 2%	N/A	300
2% to 3%	325	225
3% to 5%	250	150
5% to 7%	150	N/A
7% to 20%	100	N/A

C1	18.10.22	Spine, tarmac, detail updated for Tensor Design		J/S	RF
C2	12.09.22	Updated to construction issue		J/S	RF
REV.	NO.	DATE	DESCRIPTION	DRAWING	CHECKED
Client:					
					
MJA CIVIL & STRUCTURAL ENGINEERS Ipsium Court, 24 The Quadrant, Abingdon Service Park, Abingdon Oxon, OX14 3YS Tel: 01235 555173 Email: mail@mjaconsulting.co.uk					
Project	Boorley Green Gateway			Scale:	As Shown @ A0
Title	Highway Construction Details			Status:	CONSTRUCTION
Drawing No:	Project Engineer	MJA Project No:	6663	Date:	11/02/2022
6663 - MJA-SW-XX-DR-C-200	MF	Rev:	C2		