

PRODUCT NAME 2MXM-A9

|                         |                               |         |        |        |
|-------------------------|-------------------------------|---------|--------|--------|
| Dimensions              | Unit                          |         | Height | mm     |
|                         |                               |         | Width  | mm     |
|                         |                               |         | Depth  | mm     |
| Weight                  | Unit                          |         |        | kg     |
| Compressor              | Type                          |         |        |        |
| Operation range         | Cooling                       | Ambient | Min.   | °CDB   |
|                         |                               |         | Max.   | °CDB   |
|                         |                               |         | Nom.   | dBa    |
| Sound pressure level    | Cooling                       |         | Nom.   | dBa    |
|                         | Heating                       |         | Nom.   | dBa    |
| Refrigerant             | Type                          |         |        |        |
|                         | Charge                        |         |        | kg     |
|                         | Charge                        |         |        | tCO2Eq |
|                         | GWP                           |         |        |        |
| Piping connections      | Piping length                 | OU - IU | Max.   | m      |
|                         | Additional refrigerant charge |         |        | kg/m   |
|                         | Level difference              | IU - OU | Max.   | m      |
|                         |                               | IU - IU | Max.   | m      |
|                         |                               | System  | Actual | m      |
| Standard Accessories    | Total piping length           |         |        |        |
|                         | Installation manual           |         |        |        |
|                         | Drain plug                    |         |        |        |
|                         | Screw bag                     |         |        |        |
| Energy Efficiency Range |                               |         |        |        |
| Power supply            | Phase                         |         |        |        |
|                         | Frequency                     |         |        | Hz     |
|                         | Voltage                       |         |        | V      |
| Notes                   |                               |         |        |        |

Standard Accessories Reducer assembly  
Drain cap

**2MXM40A2V1B9**

552

852

350

36

Hermetically sealed swing compressor

-10

46

46

48

R-32

0.88

0.60

675

20 (1)

0.02 (for piping length exceeding 20m)

15

7.5

30

1

1

1

A+++ ~ D

1~

50

220-240

(1) - For one room

(2) - For combination with CVXM-A, FVXM-A - maximum piping length is 30m.

(3) - See separate drawing for operation range

(4) - See separate drawing for electrical data

(5) - Contains fluorinated greenhouse gases

**2MXM50A2V1B9**

552

852

350

41

Hermetically sealed swing compressor

-10

46

48

50

R-32

1.15

0.78

675

20 (1)

0.02 (for piping length exceeding 20m)

15

7.5

30

1

1

1

A+++ ~ D

1~

50

220-240

(1) - For one room

(2) - For combination with CVXM-A, FVXM-A - maximum piping length is 30m.

(3) - See separate drawing for operation range

(4) - See separate drawing for electrical data

(5) - Contains fluorinated greenhouse gases

**2MXM68A2V1B9**

734

974

408

60

Hermetically sealed swing compressor

-10

46

48

48

R-32

2

1.35

675

25 (1)

0.02 (for piping length exceeding 30m)

15

7.5

50

1

1

1

A+++ ~ D

1~

50

220-240

(1) - For one room

(2) - For combination with CVXM-A, FVXM-A - maximum piping length is 30m.

(3) - See separate drawing for operation range

(4) - See separate drawing for electrical data

(5) - Contains fluorinated greenhouse gases

1

3