



Sahtas Technical Data - Brookhurst handmade clay plain tiles

Technical Data: Brookhurst handmade plain tiles		
	roof	vertical
Minimum roof pitch	40°	75°
Minimum headlap	65mm	38mm
Batten spacing at maximum gauge	100mm	114mm
Size of tile	265 x 165mm	265 x 165mm
Covering capacity at maximum gauge	60 per m ²	53 per m ²
Cover width	165mm	165mm
Weight as laid	75kg per m ²	66.2kg per m ²
Battens per square metre	10 m	8.7 m
Batten size up to 600mm rafter centre	38 x 25mm	38 x 25mm
Nail size and type	40 x 3.35mm alloy clout	40 x 3.35mm alloy clout

Product sizes and quantities			
	Size (mm)	Pack quantity	Pack weight (kg)
Plain tiles	265 x 165	1120	1330
Eaves & tops tiles	265 x 185	1500	1350
Tile-and-half tiles	265 x 248	640	1330
Ornamental tiles	265 x 165	1120	1330
Bonnet hip tiles	300 x 320	560	1010
Universal valley tiles	290 x 320	590	990
Half round ridge	300 long	220	670
Hogback ridge	300 long	370	1090
Baby ridge	300 long	330	696
Third round ridge	300 long	280	784
Mono ridge	300 long	140	672
External vertical angle	265	450 (handed)	1690

Installation requirements

All Sahtas roof tiles and fittings must be installed to fully comply with the requirements of BS 5534: the British Standard Code of practice for slating and tiling and with BS 6000-6: the British Standard for workmanship on building sites. Guidance is given in the Sahtas range of installation guides - please contact us for further information and assistance.

Enquiries:

☎ 01604 434909

✉ sahtasuk@sahtas.com

🌐 www.sahtas.co.uk

Sahtas reserves the right to change products and specifications without notice. Please contact us for the latest information.

Issued: November 2018